



PolyComp

LEADERS IN LED DISPLAYS

5A Fountain Road, Eastleigh, Edenvale, Johannesburg, South Africa

Tel: +27 11 608-2770

www.polycomp.co.za



RS-A-W-YWRBG-C-6

Wired LED ROAD STUDS
product information

Overview

Improve driver awareness and road visibility at night and bad weather conditions.

Wired LED Road Studs:

5mm Wired LED SOLAR Aluminium Reflective Eye - 3 LED's per side -

RS-A-W-YWRBG-C-6



Product Details: RS-A-W-YWRBG-C-6

LED

Type:	5mm High Luminance LED.
Quantity:	3 pieces per side.
Colour:	Yellow, White, Red, Blue, Green.
Power:	12V.

Shell

Upper part:	Transparent polycarbonate.
Lower part:	Aluminium

Size:	103mm x 103mm 23mm High
-------	----------------------------


Weight:	0.33kg
---------	--------

Working Environment:	-25°C to +75°C
IP:	68
Visibility:	Approximately 800m
Certification:	CE

Packaging List:

GW:	G.W/N.W: 20.2kg/21.5kg
Carton Size:	41x28x28.5cm
Qty:	60pcs / carton

Controller



Specification	Item	Wire road studs controller	
Size	Weight	7KG	
	Dimensions	26*37*11cm	
Main components	painted control box		
	switch power supply		
	control circuit.		
	Remote PLC control		
Control working model	Lighting or flashing		
Working environment	Temperature	-25°C to 75°C	
	IP	68	
Packing list	G.W.	7.5kg	
	Carton size	30*40*15CM	
	Quantity	1pcs/box	



Hierarchical control

- 1) Install position: on the curb stone of the aisle of the both side or on the wall curbs of the aisle.
- 2) Wired road studs Install space: 10-15m, when in the curved conduit use 6-10m.
- 3) Control studs quantity: 120pcs for each controller .
- 4) Install way: Drill hole or Epoxy glue
- 5) Cable connect: T-connect, heat shrinkable silicone rubber tube and electronic to seal, so to protect the joint from water ,then water proof.



RS-A-W-YWRBG-C-6

WHAT THE PRODUCT NAME MEANS

RS-A-W-YWRBG-C-6

ROAD STUD

MATERIAL - ALUMINIUM

WIRED

LED COLOURS

CONTROLLER

NO. OF LED'S